

HUMAN CENTRIC LIGHTING

QUALITY PERFORMANCE

URBAN ELEGANCE

The architecturally-inspired shape of the PTM embodies grace and strength, creating a beautiful sculpture by day transforming into a beacon of comfort by night. Available in multiple lumen packages and distribution, PTM's elegant design and pedestrian-friendly illumination elevates the experience of the occupant in today's urban pedestrian spaces. Perfect for use in pedestrian areas such as parks, campuses, pathways, courtyards and shopping malls.

WALL MOUNT | POLE MOUNT

- MULTIPLE DISTRIBUTION
- MULTIPLE LUMEN PACKAGES
- MUTIPLE CCT OPTIONS



SLIM & VERSATILE

QUALITY CONSTTRUCTION





CONSTRUCTION

Single-piece die-cast aluminum housing with nominal wall thickness of 0.125" on a impact proof tempered glass diffuser is fully gasket with a single piece tubular silicone gasket. Toolless top opening for driver access.

FINISH

Zinc-infused TGIC thermoset powder coat finish that provides superior resistance to corrosion and weathering. Multi-stage process ensures a finish that can withstand extreme climate changes without cracking or peeling.

LISTINGS

ETL. Wet location certified. RoHs compliant, Luminaire is IP65 & IK08 rated.











MODERN | SPITZER LIGHTING
OUTDOOR

FLEXIBLE ENGINEERING


MOUNTING



WIDE DISTRIBUTION


IES, CONTROLS & ACCESSORIES

Type III



The wide distribution provides central circular or square design pattern, equally across all angles from a central point.





The wide distribution provides central circular or square design pattern, equally across all angles from a central point.





POST TOP MODERN WEB BROCHURE EDITION 1

ALAN SU, CEO

702 Interchange Boulevard Newark, DE 19711 www.spitzerlighting.com

Copyright © 2022 Spitzer Lighting. All rights reserved. Specifications are subject to change without notice. Please contact our sales team for more information.

DENNIS LUDWIG, **SALES dennis.ludwig@spitzerlighting.com**844-312-4574

MIKE LUDWIG, **SALES** mike.ludwig@spitzerlighting.com 844-312-4574