

INSTALLATION MANUAL

PRODUCT PARAMETER	
INPUT VOLTAGE	120 - 277V
DIMENSION	5", 7", 9", 12", 14"
WORKING TEMP.	-4°F~104°F




SAFETY INFORMATION

BE SURE THE POWER IS OFF! RISK OF ELECTRICAL SHOCK: Always use the switch to power off. Do not perform any operations while this unit is powered on. The electrical system you want to connect the device to must be grounded. Read the instructions before using or powering this device. The safety instructions must remain with the unit in case of transfer. Any damage to the device linked to an inappropriate use is excluded from support by the warranty. Before connecting, make sure that the current and voltage are compatible with this device. We highly recommend that all installations are made by QUALIFIED ELECTRICIAN. We are NOT responsible by any means for the use or misuse of the following information. We are NOT responsible in whole or part for any harm or damage that may or may not be caused. We reserve the right to revise the components of any product, due to part availability or change ETL, CUL, UL standards without assuming any obligation or liability to modify any products previously manufactured and without notice. These instructions do not cover all details of variations in equipment, nor do they provide every possible contingency to be met. Turn off / unplug power when installing or service device.


PRE - INSTALLATION

- Read carefully before installing fixture. Retain for future reference.
- Failure to follow instructions may result in serious injury or death
- Upon receipt the fixture, thoroughly inspect for any freight damage which should be brought to the attention of the delivery carrier. Compare the catalog description listed on the package slip with the fixture label on the housing to assure you have received material.
- This fixture must be wired in accordance with the international electrical code and applicable local codes and ordinances. Proper grounding is required to insure personal safety. Carefully observe the correct grounding procedure under installation section.


SURFACE INSTALLATION (Caution: Before beginning installation turn off the circuit breaker and light switch)



1. Fixing bracket on junction box;




2. Connecting the wire;




3. Clip or screws.


MAINTENANCE-Replacing fixture (Caution: Before beginning installation turn off the circuit breaker and light switch)



Press one side of the fixture frame (perpendicular to mounting strap then take out the fixture from the opposite side.




Don't remove the fixture from any one side of the self-lock mounting strap. this may cause damage to the fixture.



Don't remove the fixture from any one side of the self-lock mounting strap. this may cause damage to the fixture.

WIRING DIAGRAM (Caution: Before beginning installation turn off the circuit breaker and light switch)



CCT SWITCH



27K/30K/35K/40K/50K