


BRC - Compact Round Bollard


Impact proof IK10 rated PC lens with symmetrical distribution

Elegantly designed with visual-comfortable illumination performance

Optional -20°C emergency battery backup driver



SCAN ME TO
DOWNLOAD
SPEC SHEET



BLACK

DARK BRONZE



TECHNICAL SUMMARY

SIZE:	24" and 42" Overall height
WATTAGE:	20/16/12/8W
LUMEN/EFFICACY*	2000/1600/1200/800LM, 100 LM/W
INPUT VOLTAGE	120-277Vac
AVAILABLE CCT/CRI	30/40/50K changeable, 70+CRI, Custom
CONTROL	On/Off with 0-10V driver
VALIDATIONS	ETL & cETL wet location listed, IP65 and IK10 rated, RoHS, FCC compliant
LIFETIME	L70>100,000 hours, 5 year warranty
OPERATION TEMP.	-40°F ~ 122°F / -4°F ~ 122°F (with EM)
FINISH	Black, Dark Bronze, Custom

*Delivered lumen may vary, refer to photometric for full performance data




BSC - Compact Square Bollard

Impact proof IK10 rated PC lens with symmetrical distribution

Elegantly designed with visual-comfortable illumination performance

Optional -20°C emergency battery backup driver



SCAN ME TO
DOWNLOAD
SPEC SHEET

BLACK

DARK BRONZE



TECHNICAL SUMMARY

SIZE:	24" and 42" Overall height
WATTAGE:	20/16/12/8W
LUMEN/EFFICACY*	2000/1600/1200/800LM, 100 LM/W
INPUT VOLTAGE	120-277Vac
AVAILABLE CCT/CRI	30/40/50K changeable, 70+CRI, Custom
CONTROL	On/Off with 0-10V driver
VALIDATIONS	ETL wet location listed, IP65 and IK10 rated, RoHS, FCC compliant
LIFETIME	L70>100,000 hours, 5 year warranty
OPERATION TEMP.	-40°F ~ 122°F / -4°F ~ 122°F (with EM)
FINISH	Black, Dark Bronze, Custom

*Delivered lumen may vary, refer to photometric for full performance data

