

# DOWNLIGHT SERIES

**Slim Canless Swivel Downlight/** J-box included  
Color Changeable 2700K/3000K/3500K/4000K/5000K

Type:

Fixture:

## TECHNICAL DATA

PRODUCT	DRA	
SIZE	4"	6"
WATTAGE	9W	12W
LUMENS	540 LM	800 LM
EFFICACY	60 LM/W	66 LM/W
CC	2700K/ 3000K/ 3500K/ 4000K/ 5000K Color Changeable	
VOLTAGE	120V	
DIMMING	TRIAC	
CRI	>90	
TURNABLE	15° TILE	
POWER FACTOR	>0.9	
WORKING TEMP.	-5°F ~ 104°F	



## DESCRIPTION

Our Slim Canless Swivel Downlight features adjustment of 15° tilt, to allow you to direct the light to a wall that you like to highlight or adjust it downward on sloped ceilings. Canless Ultra-Slim design reduce the required clearance for the installation. Also, they are good for indoor & outdoor locations and don't require can housing for the installation anymore. With 5 color selectable feature, this downlight series satisfies most application needs in shopping centers, business buildings, hotels, airports, hospitals, and even residential areas.

## FEATURES

### CONSTRUCTION

Unit includes die-cast metal housing, LED array, heat sinks, lens, foam gasket. Junction box with integral CCT switch included. Lamp can be tilted up to 15°.

### FINISH

White finish.

### OPTICS

High quality PC lens. Efficiency LED array. Diffuse for uniform illumination.

### ELECTRICAL

High efficiency integral 120V, 60Hz constant current dimming driver. Smooth flicker free deep dimming to 5%.

### LISTINGS

Energy Star listed. ETL certification. RoHs compliant, contains no mercury or lead. Suitable for wet location. 5 year warranty.



## ORDERING INFORMATION

STANDARD ITEM: **DRA-608-5CC**

OR CUSTOMIZE BELOW:

<input type="text"/>	-	<input type="text"/>	-	<input type="text"/>
Series	Size	Lumen Package	CC	
<b>DRA</b> - (Slim Canless Swivel Downlight)	<b>4</b> - (4") <b>6</b> - (6")	<b>05</b> - (540 lm, 9W) <b>08</b> - (800 lm, 12W)	<b>5CC</b> - 5 Color Selectable (2700K/ 3000K/ 3500K/ 4000K/ 5000K)	

