

DOWNLIGHT SERIES

Ultra-Slim Baffle Canless Downlight J-box included
Color Changeable 2700K/3000K/3500K/4000K/5000K

Type:

Fixture:



TECHNICAL DATA

PRODUCT	DRB-305	DRB-406	DRB-609	DRB-815
SIZE	3"	4"	6"	8"
WATTAGE	8W	10W	12W	18W
LUMENS	500 LM	650 LM	900 LM	1500 LM
EFFICACY	62.5 LM/W	65 LM/W	75 LM/W	83 LM/W
CC	2700K/ 3000K/ 3500K/ 4000K/ 5000K Color Changeable			
VOLTAGE	120V			
DIMMING	TRIAC			
CRI	>90			
BEAM ANGLE	110°			
POWER FACTOR	0.9			
WORKING TEMP.	-5°F ~ 104°F			

DESCRIPTION

The Color Changeable Ultra-Slim Baffle Canless Downlight brings you a modern & unique lighting solution. The Canless Ultra-Slim design reduce the required of clearance for the installation. Also they are good for Indoor/Outdoor locations and dont require can housing for the installation anymore. Allows you to install them in where a recessed can wont fit, simplified installation in drywall or suspended ceilings eliminates recessed can saving time and money. With 5 color selectable feature, this downlight satisfies most application needs in a shopping center, business buildings, hotels, airports, hospitals, and residential areas.

FEATURES

CONSTRUCTION

Unit includes die-cast metal housing, LED array, heat sinks, lens, foam gasket.

FINISH

White finish.

OPTICS

High quality PC lens. Efficiency LED array. Diffuse for uniform illumination.

ELECTRICAL

High efficiency integral 120V, 60Hz constant current dimming driver. Smooth flicker free deep dimming to 5%.

LISTINGS

Energy Star listed. ETL certification. RoHs compliant, contains no mercury or lead. Suitable for wet location. 5 year warranty.



ORDERING INFORMATION


STANDARD ITEM: **DRB-406-5CC**

OR CUSTOMIZE BELOW:




Series	Size	Lumen Package	CC
DRB - (Ultra-Slim Baffle Canless Downlight)	3 - (3")	05 - (500 lm, 8W)	5CC - 5 Color Changeable (2700K, 3000K, 3500K, 4000K, 5000K)
	4 - (4")	06 - (650 lm, 10W)	
	6 - (6")	09 - (900 lm, 12W)	
	8 - (8")	15 - (1500 lm, 18W)	


DRB-305



DRB-406



DRB-609



DRB-815

