

DOWNLIGHT SERIES

Slim Canless Gimbal Downlight/ J-box included
Color Changeable 2700K/3000K/3500K/4000K/5000K

Type:

Fixture:



TECHNICAL DATA

PRODUCT	DRG	
SIZE	3"	4"
WATTAGE	6W	9W
LUMENS	370 LM	540 LM
EFFICACY	61 LM/W	60 LM/W
CC	2700K/ 3000K/ 3500K/ 4000K/ 5000K Color Changeable	
VOLTAGE	120V	
DIMMING	TRIAC DIMMING	
CRI	>90	
TURNABLE	25° TILT	
POWER FACTOR	>0.9	
WORKING TEMP.	-5° ~ 104°F	

DESCRIPTION

Our Slim Canless Gimbal Downlights feature adjustment of 25° tilt, allow you to direct the light to the object that you like to highlight or adjust it downward on sloped ceilings. Canless Ultra-Slim design reduce the required clearance for installation. Also they are good for indoor and outdoor locations and doesn't require can housing for installation anymore. With 5 color selectable feature, this downlight is popular in shopping centers, business buildings, hotels, airports, hospitals, and residential areas.

CONSTRUCTION

Unit includes die-cast metal housing, LED array, heat sinks, lens, foam gasket. Junction box with integral CCT switch included. Lamp can be tilted up to 25°.

FINISH

White finish.

OPTICS

High quality PC lens. Efficiency LED array. Diffuse for uniform illumination.

ELECTRICAL

High efficiency integral 120V, 60Hz constant current dimming driver. Smooth flicker free deep dimming to 5%.

LISTINGS

ETL certification. Suitable for wet location. 5 year warranty.



ORDERING INFORMATION

[]	-	[]	-	[]
Series	Size	Lumen Package	CC	
DRG - (Slim Canless Gimbal Downlight)	3 - (3") 4 - (4")	05 - (540 lm, 9W)	5CC - 5 Color Changeable (2700K, 3000K, 3500K, 4000K, 5000K)	

