

# DOWNLIGHT SERIES

## Smooth Recessed Downlight Retrofit

Color Changeable 2700K/3000K/3500K/4000K/5000K

Type:

Fixture:



### TECHNICAL DATA

PRODUCT	DRRS-407	DRRS-611
SIZE	4"	6"
WATTAGE	10W	14W
LUMENS	750 LM	1100 LM
EFFICACY	75 LM/W	78 LM/W
CC	2700K/ 3000K/ 3500K/ 4000K/ 5000K Color Changeable	
VOLTAGE	120V	
DIMMING	TRIAC	
CRI	>90	
BEAM ANGLE	95°	
POWER FACTOR	0.9	
WORKING TEMP.	-5°F ~104°F	

### DESCRIPTION

The Color Changeable Smooth Recessed Downlight Retrofit can be fitted in a standard recessed can housing without any modification. With the 5 color changeable temperature technology you can choose your most favorite environment color temperature without changing the lamp. Our recessed downlight is energy star and ETL certified. With 90+ CRI, provides perfect light performance, showing true colors of objects and surroundings. You get all other benefits of LED technology. Including longer life to decreased maintenance cost, less heat for better energy saving in summer.

### FEATURES

#### CONSTRUCTION

Unit includes die-cast metal housing, LED array, heat sinks, lens foam gasket.

#### FINISH

White finish.

#### OPTICS

High quality PC lens. Efficiency LED array. Diffuse for uniform illumination.

#### ELECTRICAL

High efficiency integral 120V, 60Hz constant current dimming driver. Smooth flicker free deep dimming to 5%.

#### LISTINGS

Energy Star listed. ETL certification. RoHs compliant, contains no mercury or lead. Suitable for wet location. 5 year warranty.




### ORDERING INFORMATION

STANDARD ITEM: **DRRS-407-5CC**

OR CUSTOMIZE BELOW:

[ ]	-	[ ]	-	[ ]
Series		Size		Lumen Package
DRRS - (Color Changeable Smooth Recessed Downlight Retrofit)		4 - (4 in)		07 - (750 lm , 10W)
		6 - (6 in)		11 - (1100 lm, 14W)
				CC
				5CC - Color Changeable (2700K, 3000K, 3500K, 4000K, 5000K)

#### DRRS-611



#### DRRS-407

