

# WALL PACK SERIES

## Mini Wall Pack Luminaire

Type:

Fixture:



### TECHNICAL DATA

PRODUCT	WP03A-26W
WATTAGE	26W
LUMENS	2595 LM
EFFICACY	100 LM/W
VOLTAGE	120V-277V
CRI	>70
CCT	5000K
EFFICIENCY	96%
POWER FACTOR	>0.9
THD	<15%
WORKING TEMP.	-40°F ~ 104°F

### FEATURES




### DESCRIPTION

The Mini Wall Pack is an excellent choice for needing high light transmittance from a compact fixture. Its sleek design allows for more than just alleyways and backs of buildings. Good looks lend it to be used where it can be seen and be more eye-pleasing.

### INTENDED USE

Wall Pack series is ideal for illuminating alleyways, commercial doorways, apartment and residential entrance/exits.

### DIMENSION



### ORDERING INFORMATION

STANDARD ITEM: **WP03A-26W-277-50K**  
OR CUSTOMIZE BELOW:

□	-	□	-	□	-	□
Series		Wattage		Voltage		CCT
<b>WP03A</b> - (Semi Cut-Off Wall Pack)		<b>26W</b>		<b>277</b> - (100-277V)		<b>50K</b> - (5000K)

### CONSTRUCTION

Precision die-cast aluminum housing, photocell included.

### ELECTRICAL

Class 2, constant Current, 100V-277V, 50-60 Hz.

### FINISH

Bronze finish. Rust and corrosion proof with polyester powder coating.

### LISTINGS

ETL certified. Luminaire is IP65 rated. DLC listed.

### OPTICS

Vandal-resistant polycarbonate textured opaque for low glare flat lens.